(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 27 May 2004 (27.05.2004)

PCT

(10) International Publication Number WO 2004/044424 A1

(51) International Patent Classification⁷: 43/08

F04B 43/09,

(21) International Application Number:

PCT/IL2003/000947

(22) International Filing Date:

12 November 2003 (12.11.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

152865

14 November 2002 (14.11.2002) I

- (71) Applicant (for all designated States except US): Q-CORE LTD. [IL/IL]; "Beit Legav", 24 Ben Gurion Street, 52573 Ramat Gan (IL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): BEN SHALOM,
 Zvi [IL/IL]; Ha'Chartzit 33, P.O. Box 2724, 81514 Yavne
 (IL). GOLDOR, Ori [IL/IL]; Ha'Shesek 20, P.O.Box 1519, 37808 GIVAT ADA (IL). SHABAT, Roni [IL/IL];


19350 Kibbutz Izrael (IL). **OZERI, Shaul** [IL/IL]; Gorinman 42, Ramat-Aviv, 69972 Tel-aviv (IL).

- (74) Agent: REINHOLD COHN AND PARTNERS; P.O. Box 4060, 61040 Tel Aviv (IL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report

[Continued on next page]



(57) Abstract: A pump for generating fluid flow in an elastic tubular conduit. The pump comprises a plurality of electrically operated valves, each valve being positionable adjacent to the conduit. Each valve has a valve head configured to alternate from a first position in which the lumen of the conduit adjacent to the valve head is unobstructed and a second position in which the lumen of the conduit adjacent to the valve head is obstructed. The pump also comprises a driver configured to control the positions of the valve heads, so as to execute a predetermined temporo-spatial array of valve head positions.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.